

# CARBON MONOXIDE ALARM INTERCONNECTED

WIRELESS RF CONNECTIVITY



Brilliant's carbon monoxide alarms help protects against the dangers of deadly carbon monoxide levels in the home and provides continuous monitoring of CO levels. It can be installed on walls, shelves or tabletops for added convenience. The small, sleek design make it suitable for all living areas, caravans or mobile homes.

Wireless interconnectivity, surface mount carbon monoxide alarm

Battery operated (4 x AA's included)

Proven electrochemical sensor

Stand alone unit, or wirelessly interconnect up to 22 smoke and/or carbon monoxide units

Easy to use large Test/Hush button

Pre-alarm indication gives early warning of CO

Piezoelectric horn that is rated at 85 decibels at a minimum of 3 meters.

Three LED's to indicate power, alarm and faults

Carbon monoxide is a colourless, tasteless and odourless gas that is produced when fossil fuels such as coal, oil, natural gas, LPG, charcoal and wood are not burned efficiently. It can be produced from poorly maintained or badly fitted domestic heating appliances such as boilers, wall heaters, wood burners, blocked flues or exhaust vents.

The symptoms of CO poisoning include headaches, sickness, tiredness and muscle pain - all of which can easily be misdiagnosed as flu. It is therefore important to protect your family and home with a carbon monoxide alarm.

#### APPLICATIONS

• Early detection of carbon monoxide leakage



## CARBON MONOXIDE ALARM INTERCONNECTED

INSTALLATION

### WIRELESS RF CONNECTIVITY

### **TECHNICAL SPECIFICATIONS**

Brilliant

Operating Current:	< 40mA at 3V	Do-it-Yourself installation		
Standby Power:	< 10mW			
Power source:	4 x 1.5V AA Battery (replaceable)	Wall mount		
Sensor:	CO Electrochemical Sensor	INTERCONNECT TO (sold separately)		
Operation:	Stand-alone or interconnect up to 22 smoke/CO units			
Response Time:	<50 PPM (no alarm in 120 minutes) 50-99 PPM (≤80 minutes) 100-299 PPM (≤30 minutes) >300 PPM (≤50 seconds)	Smart WiFi Interconnect Smoke Alarm 21927/05		
Alarm Sound:	85dB at 3m minimum			
Alerts:	Sound: Alarm Visual: Power/Normal (Green LED) Fault Warning (Yellow LED flashes 2 times) Low Battery (Yellow LED flashes 3 times) CO Warning Signal (Red LED) Digital Display: Carbon monoxide concentration	Interconnect Smoke Alarm 21926/05		
Function:	Hush Function Self-test of CO detection Local alarm	Finder Contraction		
Low Battery Alert:	Beeps once every 40 seconds (main alarm) Beeps once every 3 hours if alarm in interconnected	- Contracting and the second s		
Radio Frequency Info:	RF 433.92MHz wireless connection 30m indoor use line of sight 100m in free field			
Control:	Button for pairing/interconnectivity Button for test/ hush function	CO Alarm with		
Construction:	UV Stabilized fire retardant ABS / Polycarbonate	Digital Display CO Alarm		
IP Rating:	IP20 (indoor use only)			
Operating Temperature:	5C - 40C			
Humidity Range:	$5 \sim 95\%$ relative humidity (non-condensing)			
Warranty:	2 Year Replacement	130 130		
Standards:	EN50291-1:2018			

	MODEL	COLOUR	DESCRIPTION	BOX SIZE	GROSS WEIGHT	BOX QTY	BARCODE/TUN
RETAIL BOX	21929/05	White	Interconnected CO Alarm w/Digital Display	W150 x D52 x H80mm	0.24 kg	1 pc	9 312641 219293 >
INNER CTN	21929/05	White	Interconnected CO Alarm w/Digital Display	W485 x H300 x D380 mm	2.10 kg	8 pc	19312641219290
OUTER CTN	21929/05	White	Interconnected CO Alarm w/Digital Display	W485 x H300 x D380 mm	8.40 kg	32 pc	29312641219297
RETAIL BOX	21930/05	White	Interconnected CO Alarm	W150 x D52 x H80mm	0.24 kg	1 pc	9 312641 219309 >
INNER CTN	21930/05	White	Interconnected CO Alarm	W485 x H300 x D380 mm	2.10 kg	8 pc	19312641219306
OUTER CTN	21930/05	White	Interconnected CO Alarm	W485 x H300 x D380 mm	8.40 kg	32 pc	29312641219303