



INTERCONNECTED SMOKE ALARM


SMART WIFI & WIRELESS RF CONNECTIVITY



2.4 GHz



RF 433MHz



85dB



PHOTO
ELECTRIC
SENSOR



BUILT-IN
LITHIUM
BATTERY



UP TO
22
UNITS



10YR
LIMITED
WARRANTY

The Brilliant Interconnected Smoke Alarm (22653) is a hard-wired fitting that can connect wirelessly to our range of Battery-Operated Alarms using Radio Frequency. The interconnectedness allows you to link different alarms, so that if one is triggered, they can all sound (up to 22).

- Wireless interconnectivity, Ceiling mounted smoke alarm
- Powered by 10 year lithium battery (non-replaceable)
- Photoelectric sensing technology
- Fully supervised, secured and monitored via wifi
- ActivFire certified, Activfire AS3786, ISO 8201

APPLICATIONS

- Early detection of smouldering fires and open fires



Smoke Alarm
Remote Control
(Not included)
22654/05



INTERCONNECTED SMOKE ALARM

SMART WIFI & WIRELESS RF CONNECTIVITY

TECHNICAL SPECIFICATIONS

Operating Voltage:	220-240V + DC3V back up (Lithium battery)
Standby Power:	< 0.2W
Power source:	3VDC Sealed Lithium Battery (10-Year)
Sensor:	Photoelectric
Alarm Sound:	>85dB/3M
Alerts:	Alarm: RED LED flashes rapidly three times with three long "beep" every 1.5 seconds.
Hush Function:	Silences alarm for 9 minutes. LED keeps flashing.
Low Battery Alert:	Red LED flashes once every 60 seconds with low "beep" replacing alarm.
Fault:	Yellow LED flashes twice every 60 seconds, with two "beeps" replacing alarm.
Radio Frequency Info:	RF 433MHz wireless connection
Construction:	UV Stabilized fire-retardant ABS / Polycarbonate
IP Rating:	IP20 (indoor use only)
Operating Temperature:	10 to +50 degrees
Humidity Range:	0%~95%RH (No condensation)
Warranty:	10 year (for battery) / 5 year (for components)
Standards:	Activfire AS3786, ISO 8201

INSTALLATION

Must be installed by a licensed Electrician

Ceiling mounted

INTERCONNECT TO (sold separately)

WiFi interconnect smoke alarm
21927/05



Rf interconnect carbon monoxide alarm
21929/05







Rf interconnect carbon monoxide alarm
21930/05



WI-FI SYSTEM

RF SYSTEM



	MODEL	COLOUR	DESCRIPTION	BOX SIZE	GROSS WEIGHT	BOX QTY	BARCODE/TUN
RETAIL BOX	22653/05	White	240v Hardwired Interconnected Smoke Alarm	W87 x D142 x H142mm	0.4 kg	1 pc	 9 312641 226536 >
RETAIL BOX	22654/05	White	Rf Remote Control for Interconnected Smoke & Co Alarms	W74 x D54 x H114mm	0.06 kg	1 pc	 9 312641 226543 >